

Nayax

UNO-Mini

小巧、非接触式、经认证

UNO - Mini 设计超紧凑，价格实惠，是制造商将非接触式 EMV 技术集成到其终端和机器中最简便的方式



认证

通过 EMV 1 级、2 级和 3 级认证



空间高效

硬件和机械集成简单



可定制

软件集成快速简便



价格亲民

在不牺牲质量的前提下价格实惠



前沿技术

OEM的理想选择



兼容性强

适用于 Linux、Windows 和 Android 的软件开发工具包 (SDK)

支持所有支付方式

- ✓ 借记卡和信用卡
- ✓ 移动支付和 NFC 支付
- ✓ 非接触式支付
- ✓ 预付卡和封闭式环境解决方案



Main Specifications

Power	5-12VDC 0.7w in Idle, 3WPeak
CPU	Arm® 32-bit Cortex®-M33 with TrustZone® and enhanced security features
CPU Speed	160Mhz
CPU memory	Flash -2MB RAM -786KB
External memory	Flash - 8MB
Host comms	USB2.0 FS UARTTTL
Contactless EMV	EMVCo L1 v3.x compatible, Full NFC support (including card emulation)
Security	<ul style="list-style-type: none"> • 2 AES coprocessors, including one with DPA resistance • Public key accelerator, DPA resistant • True random number generator, NIST SP800-90B compliant
SAM interfaces	x1 (micro SAM)
LEDs	4 green (EMV)
Temperature	-35°C to 85°C
Humidity	Humidity (non-condensing): 10%-95%
Dimensions H x W x D (mm)	49.5 x 49.5 x 10.8/13.4
Connectors	Main connector: Molex5054330871 (8 pins) 1 x microSIM (3FF)
Regulatory	FCC, CE, UL, RoHS,TQM